

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of claims:

1. (Currently Amended) A device, comprising:
a database of radio frequency information stored as a function of radio frequency; and
a circuit coupled to the database and operating one or more algorithms for accessing the database as a function of an input radio frequency signal and generating a display signal as a function of ~~[[an]]~~ the input radio frequency signal and a current position signal for an aircraft, the display signal including aircraft communication information and aircraft navigation information from the database.
2. (Cancelled)
3. (Previously Presented) The device of claim 1, further comprising a display coupled to the circuit, the display structured to receive the display signal and display the radio frequency information.
4. (Previously Presented) The device of claim 1, wherein the circuit is a processor.
5. (Currently Amended) An aircraft frequency identifier device for an aircraft, comprising:
a database of stored radio frequency information; and
a processor coupled to the database and operating one or more algorithms for generating a display signal as a function of an input radio frequency signal and a current

position signal for the aircraft, the display signal including aircraft communication information and aircraft navigation information from the database.

6. (Currently Amended) The device of claim 5 wherein the one or more algorithms operated by the processor access the database as a function of ~~[[an]]~~ the input radio frequency signal and ~~[[a]]~~ the current position signal for the aircraft.

7. (Currently Amended) The device of claim 6 wherein the one or more algorithms operated by the processor retrieve from the database a portion of the radio frequency information corresponding to ~~[[an]]~~ the input radio frequency signal and ~~[[a]]~~ the current position signal for the aircraft.

8. (Original) The device of claim 7, further comprising a display coupled to the processor for receiving the display signal and generating a display as a function thereof.

9. (Original) The device of claim 8, further comprising a control device structured to input a radio frequency to one of the processor and the display.

10. (Currently Amended) A device, comprising:
a database of radio frequency information stored as a function of radio frequency and a current position of an aircraft; and
a processor having a first input structured to receive a signal indicative of an input radio frequency and a second input structured to receive a signal indicative of the current position of the aircraft, the processor coupled to the database and operating one or more algorithms for retrieving a portion of the radio frequency information as a function of a signal indicative of an input radio frequency received on the first input and a signal indicative of the current position of the aircraft received on the second input, the portion of the radio frequency information including aircraft communication information and aircraft navigation information.

11. (Original) The device of claim 10 wherein the processor further operates one or more algorithms for generating a display signal indicative of the portion of the retrieved radio frequency information.

12. (Original) The device of claim 11, further comprising a display coupled to receive the display signal.

13. (Original) The device of claim 11, further comprising a control device coupled to the first input of the processor and structured to input a radio frequency to the processor.

14. (Original) The device of claim 11, further comprising a control device coupled to the first input of the processor and structured to input a radio frequency to the display.

15. (Currently Amended) The device of claim 11 wherein the second input of the processor is structured to receive an output signal of a global positioning system that is indicative of the current position of the aircraft.

16. (Currently Amended) An aircraft frequency identifier, comprising:
a means for storing radio frequency information;
an accessing means, coupled to the storing means, for accessing the stored radio frequency information as a function of an input radio frequency signal and a current position signal for an aircraft; and
an output signal generating means, coupled to the accessing means, for generating an output signal as a function of the accessed radio frequency information, the output signal including aircraft communication information and aircraft navigation information.

17. (Original) The device of claim 16 wherein the means for storing radio frequency information includes means for storing the radio frequency information in a look-up table.

18. (Original) The device of claim 17 wherein the accessing means includes a means for operating one or more algorithms for retrieving the radio frequency information from a look-up table.

19. (Original) The device of claim 16, further including receiving means, coupled to the output signal generating means, for receiving the output signal.

20. (Original) The device of claim 19, further including displaying means, coupled to the output signal receiving means, for displaying the accessed radio frequency information.

21. (Original) The device of claim 16, further including signal inputting means, coupled to the output signal accessing means, for inputting a radio frequency signal.

22. (Currently Amended) A device, comprising:

database means for storing radio frequency information as a function of radio frequency and a current position of an aircraft; and

processor means for receiving a first signal indicative of an input radio frequency and a second signal indicative of the current position of the aircraft, the processor means coupled to the database means for retrieving a portion of the radio frequency information as a function of a first signal indicative of an input radio frequency and a second signal indicative of the current position of the aircraft, the portion of the radio frequency information including aircraft communication information and aircraft navigation information.

23. (Original) The device of claim 22 wherein the processor means for retrieving a portion of the radio frequency information further includes processor means for operating one or more algorithms for retrieving a portion of the radio frequency information.

24. (Original) The device of claim 23 wherein the processor means further includes signal generating means for generating a signal indicative of the portion of the radio frequency information retrieved by the processor means.

25. (Original) The device of claim 24, further comprising display means, coupled to the processor means, for receiving the signal indicative of the portion of the radio frequency information and displaying the portion of the radio frequency information.

26. (Currently Amended) A method of identifying an aircraft frequency, comprising:

- storing radio frequency information;
- accessing the stored radio frequency information as a function of an input radio frequency signal and a current position signal of an aircraft; and
- generating an output signal as a function of the accessed radio frequency information, the output signal including aircraft communication information and aircraft navigation information.

27. (Original) The method of claim 26 wherein the storing radio frequency information includes storing the radio frequency information in a look-up table.

28. (Original) The method of claim 27 wherein the accessing the stored radio frequency information includes operating one or more algorithms for retrieving the radio frequency information from a look-up table.

29. (Currently Amended) The method of claim 26, further including receiving the output signal ~~the output signal~~ and displaying the accessed radio frequency information.

30. (Original) The method of claim 26, further including inputting a radio frequency signal for use in the accessing the stored radio frequency information.

31. (Original) The method of claim 30, further including inputting a position signal for use in the accessing the stored radio frequency information.

32. (Currently Amended) A method of identifying an aircraft frequency, comprising:

storing radio frequency information in a database as a function of radio frequency and a current position of an aircraft;

receiving in a processor a first signal indicative of an input radio frequency and a second signal indicative of the current position of the aircraft; and

retrieving from the database a portion of the radio frequency information as a function of a first signal indicative of an input radio frequency and a second signal indicative of position, the portion of the radio frequency information including aircraft communication information and aircraft navigation information.

33. (Currently Amended) The method of claim 32 wherein the retrieving ~~[[a]]~~ the portion of the radio frequency information further includes operating one or more algorithms for retrieving ~~[[a]]~~ the portion of the radio frequency information.

34. (Original) The method of claim 33, further including generating a signal indicative of the portion of the retrieved portion of the radio frequency information.

35. (Original) The method of claim 34, receiving the signal indicative of the retrieved portion of the radio frequency information and displaying the retrieved portion of the radio frequency information.

36. (Currently Amended) A method of providing information to a user, the method comprising:

manually tuning a radio to a desired frequency;
receiving current position information for an aircraft;
accessing a database having information corresponding to multiple frequencies, wherein a subset of such information associated with the manually tuned frequency at the received current position information for the aircraft is retrieved as function of the manually tuned frequency and the current position information for the aircraft, the subset of such information including aircraft communication information and aircraft navigation information; and

displaying the subset of information in conjunction with the manually tuned frequency.

37. (Currently Amended) A method of providing information to a user, the method comprising:

manually tuning a radio to a desired frequency; receiving current position information for an aircraft;

accessing a database having radio frequency information corresponding to multiple frequencies at various locations, wherein a subset of such radio frequency information associated with the manually tuned frequency at the received current position information for the aircraft is retrieved as function of the manually tuned frequency and the current position information for the aircraft, the subset of radio frequency information including aircraft communication information and aircraft navigation information; and

Serial No.: 09/902,968

Filing Date: 7/10/2001

Attorney Docket No. H0001393-5542

Title: AIRCRAFT FREQUENCY IDENTIFICATION

displaying the subset of radio frequency information in conjunction with the manually tuned frequency.